

NOTES:


- 1. SUBSTRATE: N-BK7
- 2. S2 TO BE PARALLEL WITH S1 TO < 1 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2: NONE



- 5. RoHS COMPLIANT
- 6. TRANSMITTED WAVEFRONT (P-V): $\lambda/4$ (per inch over clear aperture)







FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2
SHAPE	PLANO	PLANO
SURFACE QUALITY	60-40	60-40
CLEAR APERTURE	Ø45.00	Ø45.00
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED
•		

	1	
THIRD ANGLE PROJECTION	\bigcirc	TITLE
	l	
ALL DIMS IN	mm	DWG

50mm DIA., 1mm THICK, UNCOATED λ/4 N-
BK7 WINDOW

Edmund Optics®

 DIMS IN
 mm
 DWG NO
 34427
 SHEET 1 OF 1